

# BARRE CROMATE

## GAMMA DIMENSIONALE

Diametro		Peso	Tol. f7
(mm)	(pollici)	(kg/m)	(μ)
6		0,22	-10 -22
8		0,39	-13 -28
10		0,62	-13 -38
12		0,89	-16 -34
13		1,04	-16 -34
14		1,21	-16 -34
15		1,39	-16 -34
16		1,58	-16 -34
17		1,78	-16 -34
18		2,00	-16 -34
19,05	3/4'	2,24	-20 -41
20		2,47	-20 -41
22		2,98	-20 -41
24		3,55	-20 -41
25		3,85	-20 -41
25,4	1'	3,98	-20 -41
26		4,17	-20 -41
28		4,83	-20 -41
30		5,55	-20 -41
32		6,31	-25 -50
35		7,55	-25 -50
36		7,99	-25 -50
38		8,90	-25 -50
38,1	1 - 1/2'	8,95	-25 -50
40		9,86	-25 -50
42		10,87	-25 -50
44,45	1 - 3/4'	12,18	-25 -50
45		12,48	-25 -50
50		15,41	-25 -50
50,8	2'	15,91	-30 -60

Diametro		Peso	Tol. f7
(mm)	(pollici)	(kg/m)	(μ)
52		16,67	-30 -60
55		18,65	-30 -60
56		19,33	-30 -60
60		22,19	-30 -60
63		24,46	-30 -60
63,5	2 - 1/2'	24,84	-30 -60
65		26,04	-30 -60
70		30,20	-30 -60
75		34,67	-30 -60
76,2	3'	35,77	-30 -60
80		39,45	-30 -60
85		44,53	-36 -71
88,9	3 - 1/2'	48,69	-36 -71
90		49,93	-36 -71
95		55,63	-36 -71
100		61,64	-36 -71
101,6	4'	63,60	-36 -71
105		67,96	-36 -71
114,3	4 - 1/2'	80,49	-36 -71
115		81,52	-36 -71
120		88,76	-36 -71
125		96,31	-43 -83
127	5'	99,39	-43 -83
130		104,17	-43 -83
140		120,81	-43 -83
150		138,69	-43 -83
160		157,80	-43 -83
170		178,14	-43 -83
180		199,71	-50 -96
200		246,56	-50 -96

\* Altre dimensioni su richiesta/Tolleranze speciali su richiesta